



\*ALTERNATIVE ENCODER CABLES ARE AVAILABLE WITH LENGTHS OF: 12, 24, 72, 120, 240, OR 360 INCHES. CUSTOM LENGTHS ON REQUEST.

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ACCURATE TECHNOLOGY, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ACCURATE TECHNOLOGY IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	ACCURATE TECHNOLOGY INC
DIMENSIONS ARE IN MM TOLERANCES: ANGULAR: MACH ±1 BEND ±2 ONE PLACE DECIMAL ±0.02 TWO PLACE DECIMAL ±0.01		DRAWN MF	1/1/2011	
INTERPRET GEOMETRIC TOLERANCING PER:		CHECKED		TITLE:
MATERIAL		ENG APPR.		ProScale Model 250
FINISH		MFG APPR.		
DO NOT SCALE DRAWING		Q.A.		SIZE
		COMMENTS:		DWG. NO.
				Installation Dimensions
				REV
				A
				SCALE: 1:3
				WEIGHT:
				SHEET 1 OF 2

## HOLE TABLE FOR MODELS 250B AND 250G

Dimensions subject to change

\*\*\*Dimensions A and B are +/- 0.020 tolerance.\*\*\*

MODEL	PHYSICAL LENGTH	MEASURING LENGTH	DIMENSION A	DIMENSION B	TOTAL HOLES
250-2	28	24	2	12	6
250-4	56	52	4	12	10
250-5	64	60	2	30	6
250-6	76	72	6	16	10
250-8	100	96	2	16	14
250-10	124	120	6	16	16
250-12	148	144	6	17	18
250-15	184	180	7	17	22
250-16	199	195	6	17	24
250-18	220	216	6	17	26
250-20	244	240	5	18	28
250-24 (MODEL 250B ONLY)	292	288	2	24	24